
ACOUSTIC PANELS





1,4

1,2

1,0

0,8

0,6

0,4

0,2

0,0

125

250

absorptiecoëfficiënt **a**∞

Acoustics

Acoustic padding based on recycled textile fibre.

100% recyclable, resistant to mould and complies with fire class B/S1/D0. Sound absorption (ISO 354): αw0.95



The frame of the all-round upholstered products is made of LVL, laminated veneer wood. LVL consists of several layers of 3mm pine veneer glued together, making it lightweight but relatively stronger than steel. The wood comes entirely from renewable, recyclable wood and is therefore very environmentally friendly. It is therefore PEFC certified and has an EPD eco-label.


frequentie (Hz)

4k



ACOUSTIC PANELS

This panel is an all-round upholstered acoustic panel that can be used universally for both single and DUO workstations. This panel is supplied without fixing material, but this is available separately if required.



Optionally; with bracket suitable as front panel for a single sit-stand desk.

specifications

sizes	width: 120, 140, 160 and 180 cm
	height: 75 cm
acoustics	recycled clothing class A (0.95αw)
fabrics	Anthracite (CLW22) Grey (CLW01)
assembly	wall is supplied without fixing material
	* bottom double wooden beam (14 cm) can be
	screwed between brackets of a DUO workstation





Disclaimer: This document has been compiled with the utmost care.

No part of this publication may be copied or reproduced without the express written consent from us may be copied or reproduced.

We are not liable for any inaccuracies or consequences of use or misuse of the information contained in this document.